

NEW

LMC Mini Facer

Manual operated flange facer

For re- machining damaged flange faces



Min int clamp cap : 25 mm (1")

Max int clam cap : 160 mm (6")

Min facing diam : 25,4 mm : 1"

Max facing diam : +/- 325 mm : 12 ¾"

Dimentional data :

Weight ready to use : 7 kg (15.4 lbs)

Overall length : +/- 330 mm (13")

Height from Flange face upward : +/- 200 mm (8 ")

Minimum swing diameter : 460 mm (18")

Delivery consisting off :

- Complete set of internal clamps from diam 25mm (1") ID to 160 mm (6")
- 2 off (easy exchangeable) feed screws i.e:
 - 1 off for Smooth finish
 - 1 off for Stock finish
- Set off handtools consisting off : Plastic Hamer , allen keys , spanners , toolbit TORX bit
- Cutting tool
- Cutting tips suitable for :
 - Carbon steel
 - Stainless steel
 - aluminium
 - alloys
 - plastic
 - ...
- Sturdy Carry / transport case with compartments for all components
- Ready to use

Flange facing made easy with the " LMC Mini Facer "

This easy to operate manual operated tool allows any technician to recondition RF / FF and other gasket seatings in situ. The internal diameter that can be clamped , is 1 " to 6" .

Due to this big range , the Mini Facer is a very valuable tool .

LenMatec prio bvba

Ambachtsstraat 7

B 3980 Tessenderlo

Belgium

Tel(+32 (0) 13 67 66 90

Fax (+)32 (0) 13 67 68 06

Mail to : info@lenmatec.be

URL : WWW.LENMATEC.BE